

LEJONKLOU

Contact information

Lejonklou HiFi AB
Nedre Slottsgatan 18
753 09 Uppsala
Sweden

Website: www.lejonklou.com
Email: info@lejonklou.com
Tel: +4670 558 0549

LEJONKLOU

Tundra Mono 3

Status Port & Trim manual

Background


- The degree of ventilation around the amplifier
- The surrounding temperature
- Long term drift (over years)

- When your Tundra has moved to a new location
- If the room temperature changes by more than 5°C
- Once a year

Position your Tundra Mono 3 in the location where it will stay and let its surroundings be normal. For instance, if a door to the ventilated compartment where it stays is normally closed when you're listening to music, then keep the door closed.

On its rear panel, Tundra Mono 3 has a 3.5 mm stereo jack marked STATUS PORT. Please make sure you **never** ever insert a pair of headphones into this jack! The voltages are not dangerous but they could potentially damage your headphones.

Plug the two banana plugs of the cable into the instrument, as the picture on the next page indicates. Then plug the 3.5 mm plug into the STATUS PORT of you Tundra Mono 3.



Play some music at your preferred listening level for at least half an hour. Then switch the instrument on by turning the dial to **nine o'clock** as in the picture above. Mute the music, so that your Tundra Mono 3 is completely silent. After about 5 seconds, your instrument should read somewhere close to 19. Turn the black TRIM knob next to the STATUS PORT until you arrive at exactly 19.0.

Please note that after your Tundra Mono 3 has been trimmed, it will very slowly “search” around the optimal value. This is intentional and can be seen as deviations of 0.1–0.2 from the optimal value. Don’t try to trim away these small variations.